

# Vitex Spray'T

## Penetrating Oil



High quality penetrating oil with great penetration for thousands of applications at home and workplace. Lubricates valves taps, springs, windows, joints, loosens rusted parts, frees blocked mechanisms and door locks, padlocks and screws. Dissolves glue, ink, adhesive stickers, displaces moisture and stops rust expansion on metallic surfaces, lessens friction on metal-stringed musical instruments, cables etc.

- Great penetration
- Excellent lubricant

### COLOURS

Available in clear transparent.

### PACKAGING

|             |        |
|-------------|--------|
| Transparent | 400 mL |
|-------------|--------|

### SPREADING RATE

8 - 9 m<sup>2</sup>/L per coat on properly prepared surfaces at film thickness of 30-35 µm.

### SURFACE PREPARATION

Surfaces must be clean, dry, and free of dust, grease, loose or flaking paint.

### APPLICATION

Shake the can well before use for at least 1 minute. Hold can at a distance of 20 cm away from the surface to be painted and press spray button firmly. Spray the selected area and allow the product to soak.

The spray can valve is self cleaning. In order to keep the valve in good shape, at the end of every application it is necessary to turn the can upside down and then push the valve until the flow of paint stops. Keep containers away from sources of ignition and heat.



### TECHNICAL CHARACTERISTICS

|         |                    |
|---------|--------------------|
| Density | 0,84 ± 0,05 Kg / L |
|---------|--------------------|

### STORAGE

Keep container out of reach of children (locked up if it possible), closed, in a well-ventilated, shady, cool place, away from electrical appliances, ignition sources and other sources of heat.

### SAFETY ADVICE

Read label before use. For further instructions - precautions see Material Safety Data Sheet.



T.Θ. 139 Ημερος Τόπος, Ασπρόπυργος Τ.Κ. 193 00  
P.O. Box 139 Imeros Topos, Aspropyrgos GR 193 00  
T. + 30 210 5589 500, F. + 30 210 4835 007, www.vitex.gr